



# Komatsu Genuine Power train Oil

Komatsu Power train Oil has been formulated to protect the drive-line in Komatsu Machines.

## Applications

- All Komatsu machines asking for products meeting KES 07.868.1

## Performance Features

- **Improved Drive-line – Protection**  
Komatsu Power train Oil has been formulated to keep the Komatsu machines in the best condition.
- **Improved compatibility to clutch system**  
The exclusive additive system delivers improved compatibility to clutch system.

## Performance Specifications

Komatsu - KES 07.868.1

## Health & Safety

Guidance on Health and Safety are available on the appropriate Komatsu product Material Safety Data Sheet.

## Protect the environment

Take used oil to an authorised collection point.

Do not discharge into drains, soil or water.

Komatsu Genuine Power train Oil		
	TO10	TO30
SAE Viscosity Grade	10W	30
Kinematic Viscosity		
@40°C mm <sup>2</sup> /s	36.0	100.0
@100°C mm <sup>2</sup> /s (ASTM D 445)	5.9	11.0
Viscosity Index (ASTM D2270)	107	98
Dyn. Viscosity		
@ -20°C mPa s	—	—
@ -25°C mPa s (ASTM D 2602)	5400	—
Total Acid Number mgKOH/g (ASTM D2896)	10.0	10.0
Sulphated Ash % (ASTM D874)	1.36	1.36
Density @ 15°C kg/cm <sup>3</sup> (ASTM D4052)	880	890
Flash Point (COC) °C (ASTM D93)	226	250
Pour Point °C (ASTM D97)	-37.5	-25.0

These characteristics are typical of current production.